

PRODUCT CODE: A2 PUBLICATION DATE: No

A237R November 2016

Resilmount A237R

Furring channel sound isolation clip

Installation Instructions


A237R SPECIFICATIONS

Width:	1-3/8"
Height (including rubber):	1-1/16
Length:	3-3/16
Max spacing between clips:	48" OC
Acoustical Design Load:	37Lbs.

SPECIFICATIONS

i ivietai mickness	Clip width x length	Height of rubber*
0.047"	1 3/8" x 3 1/8"	3/8"
,		Metal Thickness Clip width x length ' 0.047" 1 3/8" x 3 1/8"

*Height of rubber on top of clip



METAL FURRING CHANNEL SPECIFICATIONS:

Minimum: 25 Gauge with hemmed edge Depth: Max. 7/8" or 1 1/2" (32 mil.) Width at top: Max. 1 ¼" (32 mil.) Width flange to flange: Min: 2 ½" Max: 2 ¾" When splicing metal furring channel overlap 6 inches in between two Resilmount clips. Secure the channel with two 7/16" framing screws or 18 Gauge tie wire can be used.

Wood: # 8 x 2-1/2" Coarse Threads (A)

with nails. Use only approved screws.

Steel: #8, #10 or #12 x 1-5/8" Self Tapping Type S (B)

ս իիկիսուսի ինեզի իսկիս

Concrete: 3/16" x 2-1/4" Anchor Screws (C) **DO NOT** fasten Resilmount clips to framing members

$\int \frac{1 \frac{1}{4''}}{Min: 2 \frac{1}{2''} Max: 2 \frac{3}{4''}} = \int \frac{1}{7/8''}$

- В ______
- C =====

Uncontrolled copy. This document is subject to change without notice - please check with Resilmount regarding latest version prior to using. This document is subject to Studio's published terms and conditions. 1/7

2 845-388-1200

treation.

FASTENERS

sales@TMSoundproofing.com





CEILING INSTALLATION GUIDE

INSTALLATION NOTES

- Resilmount A237R shall not exceed 48" on center
- Spacing between metal furring channels shall not exceed 24"
- Fasten the Resilmount A237R to the substrate with a fastener approved for a minimum pull-out and shear of 120 Lbs.
- Locate the first row of A237R within 6 inches of one wall and within 6 inches of the opposite wall
- Metal Furring Channels are installed perpendicular to the joists.
- Install the gypsum board leaving 1/8" 1/4" thick gap around perimeter to be filled with acoustical caulk.
- Caulk around the entire perimeter of the gypsum board.

STEP 1

Review layout guidelines before starting installation of walls or ceilings (see Page 6). We suggest installing the ceiling first, before installing the walls.

STEP 2


Space Resilmount A237R so not to exceed 48" OC. Secure clips with a single fastener through the middle screw hole in the clip.

Wood: Use #8 x 2-1/2" coarse thread screws Steel: Use #8, #10, or #12 x 1-5/8" Type s Self tapping screws Concrete: Use 3/16" x 2-1/4" Tapcon or equal anchor

<u>իիսիիիիիիս-օսիիի իսիիստիիս</u>

STEP 3

Snap metal furring channel into Resilmount A237R.





Uncontrolled copy. This document is subject to change without notice - please check with Resilmount regarding latest version prior to using. This document is subject to Studico's published terms and conditions. 3/7

2 845-388-1200

sales@TMSoundproofing.com





WALL INSTALLATION GUIDE

INSTALLATION NOTES

- Resilmount A237R shall not exceed 48" on center
- Spacing between hat channels shall not exceed 24"
- Fasten the Resilmount A237R to the substrate with a fastener approved for a minimum pull-out and shear of 120 Lbs.
- Locate the bottom row of Resilmount A237R within 3" of the floor. (May be adjusted lower to accomadate installation of baseboard)
- Metal Furring Channels are installed horizontal to the floor.
- Use a level to ensure that Resilmount A237R and furring channels are installed horizontal and level
- Install the drywall vertically from the bottom up leaving a 1/8" - 1/4" thick gap around perimeter of wall to be filled with acoustical caulk. Caulk around the entire perimeter of the gypsum board.



WALL INSTALLATION GUIDE

Step 1

Review layout guidelines before starting installation of walls or ceilings (see Page 6). We suggest installing the ceiling first, before installing the walls.

Step 2


Space Resilmount A237R so not to exceed 48" OC. Secure clips with a single fastener through the middle screw hole in the clip.

Wood: Use #8 x 2-1/2" coarse thread screws Steel: Use #8, #10, or #12 x 1-5/8" Type s Self tapping screws Concrete: Use 3/16" x 2-1/4" Tapcon or equal anchor

իրվիի հիրապերին եմ իրակիր

Step 3

Snap metal furring channel into Resilmount A237R.





Uncontrolled copy. This document is subject to change without notice - please check with Resilmount regarding latest version prior to using. This document is subject to Studco's published terms and conditions. 4/7

845-388-1200

1---

sales@TMSoundproofing.com





WALL INSTALLATION GUIDE continued

Step 4

The Floor Shims are critical to ensure best results. Place 1/4" shims on floor in front of sole plate. Install the first row of drywall vertically against the wall. Attach drywall to channel following local building codes.

Note: Only remove the shims after all the gypsum board is completely screwed to all furring channels.

Step 5

Use acoustical caulk around the entire perimeter of each wall.

!

LOAD SPECIFICATION FOR A237R

Resilmount Clips are designed to carry furring channel with one or more layers of gypsum wallboard attached. The load compacity of the clips depends on the gauge of the hat channel used.

25 Gauge furring channel carries less load that 22 Gauge channel but performs better acoustically. The maximum design load capacity for the Resilmount Clips in shear (Wall Application) or in tension(Ceiling Applications) as follows. Design load calculations are based on testing loading to failure where the furring channel deforms.

Maximum Load for Wall and Ceiling	2:1 safety factor	2.5:1 safety factor*
Resilmount Clips w/25 gauge hat channel	45 lbs	36 lbs
Resilmount Clips w/22 gauge hat channel	60 lbs	48 lbs

*Suggested safety factor of 2.5:1 for more critical life safety applications.

h hours and a hours

Note: 5/8" thick gypsum wallboard weighs 2.2 lbs/sq ft. 1/2" thick gypsum wallboard weighs 1.6 lbs/sq ft.

Uncontrolled copy. This document is subject to change without notice - please check with Resilmount regarding latest version prior to using. This document is subject to Studico's published terms and conditions. 5/7

2 845-388-1200

sales@TMSoundproofing.com




h-theft




LAYOUTS ON WOOD AND METAL STUD WALLS & CEILINGS

Layouts for studs at 24" OC with 1 or 2 layers of Gypsum Board



Layouts for studs at 16" OC with 1 or 2 layers of Gypsum Board



6/7



HEIGHT



CLIP USAGE GUIDE FOR WALLS & CEILINGS

Studs at 16" OC and Furring Channel at 24" OC.

WIDTH

	1' to 4'	5' to 8'	9' to 12'	13' to 16'	17' to 20'	21' to 24'	25' to 28'	29' to 32'	33' to 36'	37' to 40'
1' to 2'	4	6	8	10	12	14	16	18	20	22
3' to 4'	6	11	14	17	20	23	26	29	32	35
5' to 6'	8	14	18	22	26	30	34	38	42	46
7' to 8'	10	18	23	28	33	38	43	48	53	58
9' to 10'	12	22	28	34	40	46	52	58	64	70
11' to 12'	14	25	32	39	46	53	60	67	74	81
13' to 14'	16	29	37	45	53	61	69	77	85	93
15' to 16'	18	33	42	51	60	69	78	87	96	105
17' to 18'	20	36	46	56	66	76	86	96	106	116
19' to 20'	22	40	51	62	73	84	95	106	117	128
21' to 22'	24	44	56	68	80	92	104	116	128	140
23' to 24'	26	47	60	73	86	99	112	125	138	151
25' to 26'	28	51	65	79	93	107	121	135	149	163
27' to 28'	30	55	70	85	100	115	130	145	160	175
29' to 30'	32	58	74	90	106	122	138	154	170	186
31' to 32'	34	62	79	96	113	130	147	164	181	198
33' to 34'	36	66	84	102	120	138	156	174	192	210
35' to 36'	38	69	88	107	126	145	164	183	202	221
37' to 38'	40	73	93	113	133	153	173	193	213	233
39' to 40'	42	77	98	119	140	161	182	203	224	245

Studs at 24" OC and Furring Channel at 24" OC.

իլովիի պրոշակվի իսվ իրավիրո

WIDTH

		1' to 4'	5' to 8'	9' to 12'	13' to 16'	17' to 20'	21' to 24'	25' to 28'	29' to 32'	33' to 36'	37' to 40'
	1' to 2'	4	7	9	11	13	15	17	19	21	23
	3' to 4'	6	10	13	16	19	22	25	28	31	34
	5' to 6'	8	14	18	22	26	30	34	38	42	46
	7' to 8'	10	17	22	27	32	37	42	47	52	57
	9' to 10'	12	21	27	33	39	45	51	57	63	69
	11' to 12'	14	24	31	38	45	52	59	66	73	80
	13' to 14'	16	28	36	44	52	60	68	76	84	92
Ŧ	15' to 16'	18	31	40	49	58	67	76	84	93	102
Ċ,	17' to 18'	20	35	45	55	65	75	85	95	105	115
HEIGI	19' to 20'	22	38	49	60	71	82	93	104	115	126
뿌	21' to 22'	24	42	54	66	78	90	102	114	126	138
	23' to 24'	26	45	58	71	84	97	110	123	136	149
	25' to 26'	28	49	63	77	91	105	119	133	147	161
	27' to 28'	30	52	67	82	97	112	127	142	157	172
	29' to 30'	32	56	72	88	104	120	136	152	168	184
	31' to 32'	34	59	76	93	110	127	144	161	178	195
	33' to 34'	36	63	81	99	117	135	153	171	189	207
	35' to 36'	38	66	85	104	123	142	161	180	199	218
	37' to 38'	40	70	90	110	130	150	170	190	210	230
	39' to 40'	42	73	94	115	136	157	178	199	220	241

2 845-388-1200

🔀 sales@TMSoundproofing.com

www.TMSoundproofing.com

7/7