



**Trademark**  
SOUNDPROOFING

## Foamtak Spray Adhesive

### Material Safety Data Sheet



MATERIAL SAFETY  
DATA SHEET

Auralex Acoustics, Inc.  
6853 Hillsdale Ct.  
Indianapolis, IN 46268

Foamtak(TM) Spray Adhesive

Copyright, 2001, Auralex

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Auralex products is allowed provided that:

- 1) the information is copied in full with no changes unless prior agreement is obtained from Auralex, and
- 2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**DIVISION:** ENGINEERED ADHESIVES

**TRADE NAME:**

Auralex(R) Foamtak(TM) Spray Adhesive

**ISSUED:** MAY 24, 2001

**SUPERSEDES:** APRIL 3, 2001

**DOCUMENT:** 10-3323-2

1. INGREDIENT	C.A.S. NO.	PERCENT		
DIMETHYL ETHER .....	115-10-6	30.0	-	40.0
PENTANE .....	109-66-0	20.0	-	30.0
NON-VOLATILE COMPONENTS - N.J.				
TRADE SECRET (T.S.) REGISTRY NO.				
04499600-5490P ++ .....	TradeSecret	20.0	-	30.0
ACETONE .....	67-64-1	7.0	-	13.0
NAPHTHOL SPIRITS .....	64742-48-9	1.0	-	5.0

**NOTE:** IN CASE OF EMERGENCY: Contact your local Poison Control Center.

The components of this product are in compliance with the chemical notification requirements of TSCA.

++ synthetic polymers, resins, filler, antioxidant, rosin and u.v. absorber. Not hazardous according to Canadian WHMIS criteria. Non-WHMIS controlling.

#### 2. PHYSICAL DATA

BOILING POINT:.....	N/A
VAPOR PRESSURE:.....	Compressed gas
VAPOR DENSITY: .....	> 2.00 Air = 1
EVAPORATION RATE:.....	2.00 Ether = 1
SOLUBILITY IN WATER: .....	nil
SP. GRAVITY:.....	0.725 Water = 1
PERCENT VOLATILE: .....	ca. 78 % by wt
pH: .....	N/D
VISCOSITY: .....	N/A

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

148 Horton Drive, Suite B  
Monsey, New York, 10952

Phone: 845.352.3200  
Fax: 845.367.4657

[www.TMSoundproofing.com](http://www.TMSoundproofing.com)



**Trademark**  
SOUNDPROOFING

## Foamtak Spray Adhesive

### Material Safety Data Sheet



MATERIAL SAFETY  
DATA SHEET

MSDS: Auralex(R) Foamtak(TM) Spray Adhesive

MAY 24, 2001

PAGE: 2 of 6

#### 2. PHYSICAL DATA (continued)

MELTING POINT..... N/D  
APPEARANCE AND ODOR: liquid in aerosol, orange, sweet/fruity odor.

#### 3. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:..... -50.00 F T.C.C.  
(Propellant)

FLAMMABLE LIMITS - LEL: ..... 1.00 % by vol

FLAMMABLE LIMITS - UEL: ..... Flammable Gas

AUTOIGNITION TEMPERATURE: ... N/D

##### EXTINGUISHING MEDIA:

Water spray, Carbon dioxide, Dry chemical, Foam

##### SPECIAL FIRE FIGHTING PROCEDURES:

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

##### UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

NFPA HAZARD CODES: HEALTH: 2 FIRE: 4 REACTIVITY: 1 AEROSOL STORAGE: 2  
UNUSUAL REACTION HAZARD: none

#### 4. REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY - MATERIALS TO AVOID:  
Heat.

HAZARDOUS POLYMERIZATION: Will Not Occur

##### HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Monoxide and Carbon Dioxide, Aldehydes, Ketones, Hydrocarbons.

#### 5. ENVIRONMENTAL INFORMATION

##### SPILL RESPONSE:

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Ventilate area. Extinguish all ignition sources. Cover with absorbent material. Collect using non-sparking tools. Place in a U.S. DOT-approved container.

##### RECOMMENDED DISPOSAL:

Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. Facility must be capable of handling aerosol cans. Dispose of empty cans in a sanitary landfill. Dispose of completely absorbed waste product in a facility permitted to accept chemical wastes.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately





**Trademark**  
SOUNDPROOFING

## Foamtak Spray Adhesive

### Material Safety Data Sheet



MATERIAL SAFETY  
DATA SHEET

MSDS: Auralex(R) Foamtak(TM) Spray Adhesive

MAY 24, 2001

PAGE: 3 of 6

#### 5. ENVIRONMENTAL INFORMATION (continued)

RECYCLE EMPTY AEROSOL CONTAINERS WHERE AVAILABLE.

ENVIRONMENTAL DATA:  
Not determined.

**REGULATORY INFORMATION:**

Volatile Organic Compounds: ca. 66 % by wt.  
VOC Less H<sub>2</sub>O & Exempt Solvents: ca. 563 gms/liter calculated per  
SCAQMD rule 443.1.  
Hazardous Air Pollutants: 0 % by wt calculated.

Since regulations vary, consult applicable regulations or authorities  
before disposal. U.S. EPA Hazardous Waste Number = D001 (Ignitable)

**EPCRA HAZARD CLASS:**

FIRE HAZARD: Yes PRESSURE: Yes REACTIVITY: No ACUTE: Yes CHRONIC: Yes

#### 6. SUGGESTED FIRST AID

**EYE CONTACT:**

Immediately flush eyes with large amounts of water. Get immediate  
medical attention.

**SKIN CONTACT:**

Flush skin with large amounts of water. If irritation persists, get  
medical attention.

**INHALATION:**

Remove person to fresh air. If not breathing, give artificial  
respiration. If breathing is difficult, get immediate medical  
attention.

**IF SWALLOWED:**

Do not induce vomiting. Drink two glasses of water. Call a physician.

#### 7. PRECAUTIONARY INFORMATION

**EYE PROTECTION:**

Avoid eye contact with vapor, spray, or mist. Wear safety glasses  
with side shields.

**SKIN PROTECTION:**

Avoid prolonged or repeated skin contact.

**VENTILATION PROTECTION:**

Do not use in a confined area or areas with little or no air  
movement. If exhaust ventilation is not adequate, use appropriate  
respiratory protection. Provide ventilation adequate to control vapor  
concentrations below recommended exposure limits and/or control spray

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately



**Trademark**  
SOUNDPROOFING

# Foamtak Spray Adhesive

## Material Safety Data Sheet



**MATERIAL SAFETY  
DATA SHEET**

MSDS: Auralix(R) Foamtak(TM) Spray Adhesive

MAY 24, 2001

PAGE: 4 of 6

### 7. PRECAUTIONARY INFORMATION (continued)

or mist.

#### RESPIRATORY PROTECTION:

Avoid breathing of vapors, mists or spray. Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: half-mask organic vapor respirator.

#### PREVENTION OF ACCIDENTAL INGESTION:

Do not ingest.

#### RECOMMENDED STORAGE:

Store at temperatures below 120 degrees F (49 degrees C). Store out of direct sunlight. Keep out of the reach of children.

#### FIRE AND EXPLOSION AVOIDANCE:

Aerosol container contains flammable gas under pressure. Keep away from heat, sparks, open flame, and other sources of ignition. Extremely flammable liquid and vapor. Do not pierce or burn container, even after use. No smoking while handling this material. Avoid static discharge.

INGREDIENTS	EXPOSURE LIMITS		TYPE	AUTH	SKIN*
	VALUE	UNIT			
DIMETHYL ETHER .....	1000	ppm	TWA	CMRG	
DIMETHYL ETHER .....	500	ppm	TWA	AIHA	
PENTANE .....	600	ppm	TWA	ACGIH	
PENTANE .....	600	ppm	TWA	OSHA	
PENTANE .....	OSHA VACATED	PEL			
PENTANE .....	750	ppm	STEL	OSHA	
PENTANE .....	OSHA VACATED	PEL			
PENTANE .....	1000	ppm	TWA	OSHA	
NON-VOLATILE COMPONENTS - N.J.					
TRADE SECRET (T.S.) REGISTRY NO.					
04499600-5490P ++					
ACETONE .....	NONE	NONE	NONE	NONE	
ACETONE .....	500	ppm	TWA	ACGIH	
ACETONE .....	750	ppm	STEL	ACGIH	
ACETONE .....	750	ppm	TWA	OSHA	
ACETONE .....	OSHA VACATED	PEL			
ACETONE .....	1000	ppm	STEL	OSHA	
ACETONE .....	OSHA VACATED	PEL			
ACETONE .....	1000	ppm	TWA	OSHA	
NAPHTHOL SPIRITS .....	100	ppm	TWA	3M	
NAPHTHOL SPIRITS .....	300	ppm	TWA	CMRG	

\* SKIN NOTATION: Listed substances indicated with "Y" under SKIN refer to the potential contribution to the overall exposure by the cutaneous route including mucous membrane and eye, either by airborne or, more particularly, by direct contact with the substance. Vehicles can alter skin absorption.

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

148 Horton Drive, Suite B  
Monsey, New York, 10952

Phone: 845.352.3200  
Fax: 845.367.4657

[www.TMSoundproofing.com](http://www.TMSoundproofing.com)



**Trademark**  
SOUNDPROOFING

## Foamtak Spray Adhesive

### Material Safety Data Sheet



MATERIAL SAFETY  
DATA SHEET

MSDS: Auralex(R) Foamtak(TM) Spray Adhesive

MAY 24, 2001

PAGE: 5 of 6

#### 7. PRECAUTIONARY INFORMATION (CONTINUED)

**SOURCE OF EXPOSURE LIMIT DATA:**

- ACGIH: American Conference of Governmental Industrial Hygienists
- AIHA: American Industrial Hygiene Assoc. Workplace Environmental Exposure Level Guideline
- OSHA: Occupational Safety and Health Administration
- OSHA: Occupational Safety and Health Administration Vacated PEL. Vacated Permissible Exposure Limits (PEL) are enforced as the OSHA PEL in some states. Check with your local regulatory authority.
- CMRG: Chemical Manufacture Recommended Guidelines
- NONE: None Established

#### 8. HEALTH HAZARD DATA

**EYE CONTACT:**

Moderate Eye Irritation: signs/symptoms can include redness, swelling, pain, tearing, and hazy vision.

**SKIN CONTACT:**

Mild Skin Irritation (after prolonged or repeated contact): signs/symptoms can include redness, swelling, and itching.

**INHALATION:**

Intentional concentration and inhalation may be harmful or fatal.

Central Nervous System Depression: signs/symptoms can include headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Irritation (upper respiratory): signs/symptoms can include soreness of the nose and throat, coughing and sneezing.

**IF SWALLOWED:**

Ingestion is not a likely route of exposure to this product.

WHILE THE FOLLOWING EFFECTS ARE ASSOCIATED WITH ONE OR MORE OF THE INDIVIDUAL INGREDIENTS IN THIS PRODUCT AND ARE REQUIRED TO BE INCLUDED ON THE MSDS BY THE U.S. OSHA HAZARD COMMUNICATION STANDARD, THEY ARE NOT EXPECTED EFFECTS DURING FORESEEABLE USE OF THIS PRODUCT.

Irritation of Gastrointestinal Tissues: signs/symptoms can include pain, vomiting, abdominal tenderness, nausea, blood in vomitus, and blood in feces.

#### SECTION CHANGE DATES

HEADING

SECTION CHANGED SINCE APRIL 3, 2001 ISSUE

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

148 Horton Drive, Suite B  
Monsey, New York, 10952

Phone: 845.352.3200  
Fax: 845.367.4657

[www.TMSoundproofing.com](http://www.TMSoundproofing.com)





**Trademark**  
SOUNDPROOFING

## Foamtak Spray Adhesive

### Material Safety Data Sheet

---



MATERIAL SAFETY  
DATA SHEET

---

MSDS: Auralex(R) Foamtak(TM) Spray Adhesive

MAY 24, 2001

PAGE: 6 of 6

Abbreviations: N/D - Not Determined N/A - Not Applicable CA - Approximately

The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. Auralex MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the Auralex product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of an Auralex product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Auralex product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

Auralex provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, Auralex makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from Auralex.

---

148 Horton Drive, Suite B  
Monsey, New York, 10952

Phone: 845.352.3200  
Fax: 845.367.4657

[www.TMSoundproofing.com](http://www.TMSoundproofing.com)