

Green Glue Noiseproofing Compound MSDS - Page 1 of 4

Material Safety Data Sheet

1. Product and Company Identification

Product name: Green Glue Noiseproofing Compound

Product type: Water-Based Damping Adhesive

2. Composition Information

Name:	CAS Number:	Percent by weight:
Latex polymer	None established	25-60%
Water	7732-18-5	30-50%
This product does not contain hazardous or carcinogenic components reportable under OSHA Hazard Communication Standard 1910.1200		

3. Hazards Identification

3.1 Emergency Overview HMIS Rating			
Appearance:	Thin, light green paste	Health:	1 (slight)
Odor:	Slight characteristic latex to no odor	Flammability:	0 (minimal)
Fire Hazard:	Not a Significant Fire Hazard	Chronic:	0 (minimal)
3.2 Potential Health Effects			
Ingestion:	Potential irritant, do not ingest		
Inhalation	Not expected to be harmful under normal conditions of use. If allowed to become airborne, may cause irritation of nose, throat and lungs		
Skin: May cause irritation on prolonged or repeated contact or if allowed to dry on skin; brief contact is not shown to cause irritation			
Eyes:	Eyes: May cause irritation		
3.3 Delayed Hazards: None known to company			

4. First Aid Measures

Immodiate I	Jozofo
Immediate Hazards	
Ingestion:	If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact Poison Control Center or hospital emergency room for any other additional treatment directions.
Inhalation	Remove to fresh air.
Skin:	In case of contact, flush with water and wash until clean. If material is noticed on skin before dry, wash prior to material drying if at all possible.
Eyes:	Immediately flush eyes with plenty of water. Call a physician if irritation persists.

148 Horton Drive, Suite B Monsey, New York, 10952

Phone: 845.352.3200 Fax: 845.367.4657



Green Glue Noiseproofing Compound MSDS - Page 2 of 4

5. Fire Fighting Measures

0 oggououoo	
Auto ignition Temperature:	Not available
Upper/Lower Flammable Limits:	Not available
Up/Lower Explosive Limits, % by Vol:	Not applicable
Flash Point:	Not available

Material is incombustible as supplied, but dried material will support combustion. In case of fire, water should be used to keep fire-exposed containers cool.

6. Accidental Release Measures

Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

7. Handling and Storage

7.1 Handling

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

7.2 Storage

Keeping from Freezing

Store in a cool, dry place

Keep containers tightly closed

8. Exposure Controls/Personal Protection

8.1 Exposure limits and controls

Exposure limits: None established

8.2 Personal protection

Inhalation: Inhalation is not anticipated to be a route of exposure in normal use. If the product is to become airborne, use NIOSH/MSHA approved respiratory protection equipment.

Skin: Wear latex or other water-impermeable gloves. Wear coveralls to prevent skin contact.

Phone: 845.352.3200

Fax: 845.367.4657

Eye: Wear safety glasses

www.TMSoundproofing.com



Green Glue Noiseproofing Compound MSDS - Page 3 of 4

9. Physical and Chemical Properties

9. Physical and Chemical Properties	
Percent Volatiles:	25-40
pH @ 25 C:	7-10
Specific Gravity:	1.03-1.08
Appearance:	Light green colored thin paste
Auto-Ignition Temperature:	Not applicable
Boiling Point:	100 deg C
Vapor Density (Air=1):	< 1
Vapor Pressure:	mm Hg @ 20 C
Evaporation Rate (Butyl Acetate=1):	< 1
Upper/Lower Flammable Limits:	Not applicable
Up/Lower Explosive Limits, % by Vol:	Not applicable
Flash Point:	Not applicable
Freezing Point:	0 deg C
Odor Threshold, ppm:	Not applicable
Solubility in Water:	Dispersible

10. Stability and Reactivity

Stability & Reactivity:	Stable
Incompatibles:	Strong acids and alkaline materials
Decomposition Products may include:	CO, CO2
Hazardous Polymerization:	Will not occur
Other Hazards:	None known

11. Toxicological Information

Chronic/Carcinogenicity:	No
LD50:	Not available

Information on analogous products shows minimal reason for concern.

12. Ecological Information

Not Determined

Information on analogous products implies that this product will not be toxic to fish or plants. Polymer is not biodegradable.

13. Disposal considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Not Regulated



Green Glue Noiseproofing Compound MSDS - Page 4 of 4

15. Regulatory Information (Selected Regulations)

15.1 U.S. Federal Regulations:	
Canadian Regulatory Information:	This product is not classified as hazardous under WHMIS.
VOC:	<5 gram per liter (calculated)

TSCA Section 8(b) Inventory

All reportable chemical substances are listed on the TSCA Inventory or is governed by CFR (Code Federal Regulation) section 40 CFR 723.250, "Benign exemption", exempting it from mandate of TSCA registry. We rely on statements of compliance from our suppliers.

16. Other Information

User's Responsibility

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Trained, educated workers are your companies' greatest safety asset.

Disclaimer

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. All claims shall be limited to purchase price only. Seller is liable in no event for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise. Seller certifies only that the information in this sheet is, to the limits of their knowledge, accurate. Seller relies to some extent on supplier data and is not responsible for errors contained therein.

Phone: 845.352.3200

Fax: 845.367.4657

10/4/2010

www.TMSoundproofing.com