



# GUILFORD OF MAINE - DASHING

## PRODUCT SPECS

### Specifications

**Content**

92% post-consumer recycled polyester  
8% pre-consumer recycled polyester

**Weight**

10.9 ± 1.0 oz./lin. yd.

**Width**

66" min. useable

**Repeat**

2" vertical | 2.4" horizontal

\* For more information, view our [Finishes brochure](#) or contact Sales Service: 800-544-0200

### Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

### Performance

**Breaking Strength (ASTM D5034)**

240 lbf min. warp and 190 lbf min. fill

**Tear (ASTM D2261)**

25 lbf min. warp and 40 lbf min. fill

**Colorfastness to light (AATCC 16.3 Option 3)**

Grade 4 min. at 40 hours

**Colorfastness to crocking (AATCC 8)**

Grade 4 min. dry & Grade 3 min. wet

**Flammability**

ASTM E84 Class I or A

### Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.



Terratex is a registered trademark of True Textiles, Inc. and designates fabrics that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life.

[www.tmsoundproofing.com](http://www.tmsoundproofing.com)

Phone: 845-388-1200 Fax: 845-388-1388